

DECLARATION OF PERFORMANCE: N° 001CPR2013-07-14

1. Identification of the product: **Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$**
2. Intended use: **for internal and external walls and floorings**
3. Name and contact of the manufacturer: **Italcer SpA SB, via Emilia Ovest 53/A - 42048 Rubiera (RE) – Italia**
4. System of assessment and verification of constancy of performance (AVCP): **System 4**
5. Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL}	EN 14411:2012
Release of dangerous substances, for: - Cadmium - Lead	NPD	
Breaking strength	Thickness $\geq 7.5\text{mm}$: $\geq 1300\text{N}$ Thickness $< 7.5\text{mm}$: $\geq 700\text{N}$	
Slipperiness	NPD	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesives, type C1	$\geq 0.5 \text{ N/mm}^2$	
Cementitious adhesives, type C2	$\geq 1 \text{ N/mm}^2$	
Dispersion adhesives	NPD	
Reaction resin adhesives	NPD	
Mortar	NPD	
Thermal shock resistance	Pass	
Durability for: -internal use: -external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 5.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and behalf of the manufacturer by:



Graziano Verdi

Amministratore Delegato

Rubiera, 23/04/2025